

# 常州联拓复合材料有限公司

## CHANGZHOU UTEK COMPOSITE CO., LTD.

FuhanYuan 1-812, New North District, Changzhou 213022, Jiangsu, China  
 T: 86-519-85856360; www.utekcomposite.com; info@utekcomposite.com

### AR CHOPPED STRAND


It is a high integrity AR glass fibre chopped strand for concrete and cement mortar.

**Product Features**

- ◎ Good workmanship
- ◎ Control and prevent cracking of fresh concrete
- ◎ Improve the durability and mechanical properties of concrete
- ◎ High dispersion
- ◎ Evenly mixed, no surface marks

**Identification:**

Glass Type	AR			
Chopped Strands	CS			
Filament Diameter(μm)	13			
Chop Length(mm)	6	12	18	24



#### Technical Parameters

Filament Diameter (%)	Moisture Content (%)	Size Content (%)	Chop length (mm)	Zirconia content (%)
ISO 1888	ISO 3344	ISO 1887	Q/JS J0361	Q/JS J0362
± 13	≤ 0.02	0.8-2	±18	≥ 16.7

#### Storage

Unless otherwise specified, the fiberglass products should be stored in a dry, cool and moisture-proof area. The fiberglass products should remain in their original package until prior to use. The room temperature and humidity should be always maintained at -10℃~35℃ and ≤80% respectively. To ensure safety and avoid damage to the product, the pallets should not be stacked more than three layers high. When the pallets are stacked in 2 or 3 layers, special care should be taken to correctly and smoothly move the top pallet.



#### Packaging

The product can be packed in bulk bags, heavy-duty box, and composite plastic woven bags; For example:  
 Bulk bags can hold 900kg-1000kg each;  
 Cardboard boxes and composite plastic woven bags can hold 15kg-25kg each.

##### Bulk bag

Length mm (in)	1030 (40.5)
Width mm (in)	1030 (40.5)
Height mm (in)	1000 (39.4)

##### Heavy-duty box

Length mm (in)	1120 (44)
Width mm (in)	1120 (44)
Height mm (in)	1050 (41.3)

##### Compositite plastic woven bag

Length mm (in)	850 (33.5)
Width mm (in)	500 (19.7)
Height mm (in)	120 (4.7)